

ROUND BALER

SALIENT FEATURES

- The guide wheels helps in maintaining the same line as per reel tines leading to accurate pickup.
- The rotor design encourages a uniform crop flow, which reduces the risk of blockages, thus maximizing output.
- Accurate height control can be achieved through a spring balanced hydraulic lifting system.
- Automatic greasing system with each bale coming out of machine leading to better operation.
- Safety slip clutch for drive overload protection.





ROUND BAILER


The worldtrac round baler is the perfect equipment that compresses the cut and raked crops, including salt marsh hay, cotton, hay, flax, and straw, turns them into compact bales making it easy in handling, storing & transporting.

TECHNICAL SPECIFICATIONS

Model Name	mimimimi i← →i Working Width (cm)	Bale Chamber (cm)	Bale Length (cm)	Bale Diameter (cm)	Bale Weight (kg)	Binding Twine	No. of Rollers	Bale Ejection	Lubrication	Efficiency (Bales per hour)	Forward	Tractor Power (HP)	PTO RPM	Dimension (LxWxH) (cm)	Approx Weight (Kg)	Tyre Size	Drive Protection
WT-RB-0.8	80	70	70	50	14-17	Jute Twine / PP	10	Automatic	Central oil lubricating system for chains	60-80	2-5	25-60	540	125x148x116	465	16 x 6.50 - 6 ply - Tubeless	Shear Bolt on Machine. Slip clutch in pickup reel
WT-RB -1.15EW	115	105	105	50	18-22		10							125x180x116	553		
WT-RB0.8J	80	70	70	60	24-28		12			40-60				140x148x132	515		
WT-RB1.03J	103	93	93	60	28-32		12							140x169x132	580		
WT-RB-1.15J	115	105	105	60	32-36		12							140x180x132	620		

NET WRAPPING SYSTEM (OPTIONAL)

Model Name	Net Wrap Material & Size	No. Of Wrapping Layers	Control	Net Feeding Method	Automatic Bale Ejection	Machine Weight (kg)
WT-RB-0.8	HDPE+UV -1.2X1100M	3-4	Ecu Driven Linear Actuator	Manual / Automatic	Manual / Automatic	510
WT-RB -1.15EW						618
WT-RB0.8J						560
WT-RB1.03J						635
WT-RB-1.15J						685





INTERNATIONAL BUSINESS OFFICE

Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) | Phone: +91 11 66 45 5200 Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221 | Fax: +91- 01882-522222 URL: www.worldtrac.in