

COMPACT DISC HARROW

DESCRIPTION

Worldtrac Compact Disc harrow is designed specifically for stubble cultivation and seedbed preparation. The compact design and aggressive disc angle ensure reliable penetration and excellent mixing in of harvest residues.





FEATURES





STRONG GREASE-ABLE BEARING HUBS







TECHNICAL SPECIFICATIONS

		Compact Disc Harrow					
•	Model Name	WT-CDH-16	WT-CDH-18	WT-CDH-20	WT-CDH-24	WT-CDH-28	WT-CDH-32
	No Of Disc	16	18	20	24	28	32
	Type Of Disc	Front Notched & Rear Plain					
	Disc Diameter (mm)	610/660- Optional					
∷ (←→)	Disc Spacing (mm)	225					
	Working Width (mm)	1750-1800	2000-2050	2250-2300	2500-2550	2750-2800	3000-3050
	Bearing Hubs	6	8	8	8	8	12
	Gang Rod (mm)	32x32					
	Mounted	CAT-II				CAT-II/CAT-III	
kg	Weight (Kg. Approx.)	700	860	980	1100	1250	1500
a 0	Tractor Power (HP)	50-60	60-70	70-80	75-90	90-100	100-120

^{*}Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

BENEFITS AND ADVANTAGES

- Sturdy structure to use the machine in challenging field conditions
- Heavy duty strong SG iron bearing hub with greasing arrangement
- Heavy duty gang axle for toughest operation
- Scrappers are provided which removes the stuck material automatically, this keeps the load on tractor in check and gives better fuel efficiency
- Specially designed mounted cum trailed drawbar gives flexibility to user to use machines according to needs and applications.