

TRAILED HYDRAULIC DISC HARROW

DESCRIPTION

Worldtrac Trailed Hydraulic Disc Harrow crushes the clods in to fine particles i.e. Better tilth as compared to standard harrow. It ensures effective cutting and mixing of stubbles weeds with better mixing of organic manure

Due to heavy structure it helps to mash some crop waste in field. Hydraulic adjustment from tires also controls the depth of disc harrow, which helps in efficient working in any kind of soil condition.

Worldtrac Trailed disc harrow is available with different disc sizes to suit the HP of prime mower.



FEATURES








HEAVY DUTY GANG AXLE

HYDRAULIC DEPTH CONTROL







TECHNICAL SPECIFICATIONS

		Trailed Hydraulic Disc Harrow			
1	Model	WT-THD-10-H	WT-THD-12-H	WT-THD-14-H	WT-THD-16-H
40	No Of Disc	20	24	28	32
40	Type Of Disc	Front Notched & Rear Plain			
	Disc Diameter (mm)	660			
8 ←>(8)	Disc Spacing (mm)	225			
nılminılml K >1	Working Width (mm)	2300	2700	3100	3500
	No. of Bearing Hubs	8			
	Gang Rod (mm)	40			
(Tyre Size	7.50-16			
	Depth Control	Hydraulically			
	Mounted	Trailer Hook			
kg	Weight (Kg. Approx.)	1650	1850	2050	2250
a ©	Tractor Power (HP)	70-80	90-100	100-110	150 & above

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

BENEFITS AND ADVANTAGES

- Split Gang shaft for ease of serviceability.
- Heavy Duty gang axle and bearing hubs to absorb sudden impact loads.
- Hydraulically controlled tires helps to control the depth of harrow uniformly throughout the field
- Notched Disc Blade improve residue cutting and soil penetration in hard ground
- Easy Hydraulic adjustment helps driver to transport quickly for faster working
- Hydraulic movement of tires help sturdy structure of machine to move across with ease in any soil condition