


DISC RIDGER

DESCRIPTION

Worldtrac Ridger is the primary soil tillage equipment which is mounted and trailed from tractor's hydraulic unit and universal 3 point linkage system. As per crop it helps in making perfect ridge and also helps in uprooting unwanted roots and weeds.



FEATURES









TECHNICAL SPECIFICATIONS

		Disc Ridger		
•	Model	WT-DR1	WT-DR2	WT-DR3
4 040	Length (mm)	910	1498	1498
THE STATE OF THE S	Width (mm)	1675	2540	3800
<u> Turk</u>	Height (mm)		1220	
ınlınlınlınlı	Working Width (mm)	Adjustable		
milmilmilmi	Working depth (mm)		150	
	No of Discs	2	4	6
	Size of Discs		660x6	
kg	Weight (Kg. Approx.)	225	440	610
∂ ©	Tractor Power (HP)	50-60	60-75	75-90

^{*}Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

BENEFITS AND ADVANTAGES

- Available in 2 bottoms, 4 bottoms & 6 Bottoms to make one ridge, two ridges & three ridges respectively.
- It has heavy duty box type frame.
- High quality boron steel disc with 48-52 HRC hardness.
- Size and depth of the ridge can be adjusted.