

GROOMING MOWER

DESCRIPTION

Grooming or finishing mowers cut wide, open areas with ease, with functions designed especially for manicuring uneven farmland. These implements help in mowing sports fields, public areas, lawns, and other large areas that need to be manicured quickly without sacrificing performance.



FEATURES



HEAVY DUTY GEARBOX



STRONGLY BUILT FRAME



HEAVY DUTY TWISTED CUTTING BLADES









TECHNICAL SPECIFICATIONS

| | | Grooming Mower |
|----------|-----------------------|-----------------------------|
| • | Model | WTGM-1.2 |
| A second | Length (mm) | 1355 |
| | Width (mm) | 1345 |
| | Height (mm) | 780 |
| | Deck Thickness (mm) | 4 |
| | Working Width (mm) | 1210 |
| | Cutting Height (mm) | 15-105 |
| 6 G | Tractor Power (HP) | 20-35 |
| 4 | 3-point Hitch Type | Cat-I/II |
| 3 | Wheel Type | Solid Tyre 10x3.25 |
| | Belt (Number & Type) | 2 SPB Type |
| • | Number of blades | 3 |
| • | Blade size (mm) | 6x60x420 |
| | Blade tip Speed (fpm) | 13585 |
| | Spindle Type | With Greasable Ball Bearing |
| | Spindle Bearings | Bearing 6206 |
| | Front roller | Standard |
| kg | Unit Weight (Kg) | 195 |

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development

BENEFITS AND ADVANTAGES

- Highly engineered & rugged gearbox with cooling fins.
- Strongly built frame for working in tough conditions.
- Twisted blades ensure high performance cutting.
- Extra wide solid rubber tyres for longer durability and stability during operation.
- Spacers for height adjustment and 360° free movement of tyres.
- Rollover wheel to avoid damages and extra support.
- Belt type 3 blades transmission with high quality alloy steel blades.