


LAND LEVELER

DESCRIPTION

Worldtrac Land Leveler results in optimum utilization of water, high speed working and reduction in weeding cost. This can level the field with tractor mounting and reduce the work in crop establishment.

FEATURES







TECHNICAL SPECIFICATIONS

		Land Leveler			
6	Model	WT-LL7	WT-LL8	WT-LL9	WT-LL10
	Overall Length (mm)	970			
	Overall Width (mm)	2165	2465	2770	3075
	Overall Height (mm)	1210			
⋣	3 Point Linkage Cat.	Cat II			
mimimimi ı←──>ı	Working Width (mm)	2140	2440	2745	3050
a @	Tractor Power (HP)	35-40	45-55	60-75	75-90
kg	Weight (Kg. Approx.)	240	270	295	330

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development

BENEFITS AND ADVANTAGES

- The robust frame, various supports like Centre support, rear support of leveler chassis, thicker plate creates a strong machine designed to work on the difficult soil conditions
- High carbon steel reversible blade ensures longevity and maximum performance
- Easy to operate machine allows operator to work back and forth which helps in filling corners of field efficiently
- Heavy duty bucket ensures uniform levelling.
- Both the sides are equipped with SOIL HOLDING ARMS to carry the soil perfectly till end without spillage.

