

BACKHOE

DESCRIPTION

The Backhoe Loader acts as a digger, loader, back filler, trencher for executing outdoor tasks on the farm. The diverse applications come with a handy attachment process and detachment in no time from the tractor.



FEATURES












TECHNICAL SPECIFICATIONS

Model Model WTBH 180 Loading Height (A) (cm / Inch) Digging Depth (B) (cm / Inch) Max Height © (cm / Inch) Digging width (D) (cm / Inch) Wax width (cm / Inch) Breakout force (kg / Ibs) Rotation angle (degree) Pump capacity (L/m) Ground Clearance (mm / inch) Backhoe WTBH 180 150 / 59 180 / 70.9 225 / 88.6 180 Pump capacity (L/m) 180			
Loading Height (A) (cm / Inch) Digging Depth (B) (cm / Inch) Max Height © (cm / Inch) Digging width (D) (cm / Inch) Max width (cm / Inch) Breakout force (kg / Ibs) Rotation angle (degree) Pump capacity (L/m) 150 / 59 180 / 70.9 225 / 88.6 1500 / 3307			Backhoe
Digging Depth (B) (cm / Inch) Max Height © (cm / Inch) Digging width (D) (cm / Inch) Max width (cm / Inch) Breakout force (kg / Ibs) Pump capacity (L/m) 180 Ground Clearance (mm / inch) 300 / 11.8	•	Model	WTBH 180
Max Height © (cm / Inch) Digging width (D) (cm / Inch) Max width (cm / Inch) Breakout force (kg / Ibs) Rotation angle (degree) Pump capacity (L/m) 18 Ground Clearance (mm / inch) 300 / 11.8		Loading Height (A) (cm / Inch)	150 / 59
Digging width (D) (cm / Inch) 247 / 97.2 Max width (cm / Inch) 225 / 88.6 Breakout force (kg / Ibs) 1500 / 3307 Rotation angle (degree) 180 Pump capacity (L/m) 18 Ground Clearance (mm / inch) 300 / 11.8		Digging Depth (B) (cm / Inch)	180 / 70.9
Max width (cm / Inch) 225 / 88.6 Breakout force (kg / Ibs) 1500 / 3307 Rotation angle (degree) 180 Pump capacity (L/m) 18 Ground Clearance (mm / inch) 300 / 11.8		Max Height © (cm / Inch)	225 / 88.6
Breakout force (kg / lbs) 1500 / 3307 Rotation angle (degree) 180 Pump capacity (L/m) 18 Ground Clearance (mm / inch) 300 / 11.8		Digging width (D) (cm / Inch)	247 / 97.2
Rotation angle (degree) Pump capacity (L/m) Ground Clearance (mm / inch) 300 / 11.8		Max width (cm / Inch)	225 / 88.6
Pump capacity (L/m) 18 Ground Clearance (mm / inch) 300 / 11.8		Breakout force (kg / lbs)	1500 / 3307
Ground Clearance (mm / inch) 300 / 11.8		Rotation angle (degree)	180
Durana (1.2)		Pump capacity (L/m)	18
Pressure (bar) 180		Ground Clearance (mm / inch)	300 / 11.8
		Pressure (bar)	180
Bucket Size included (cm / Inch) Series 1 // 30/12			Series 1 // 30/12
3 Point Hitch Cat I	<u> </u>	3 Point Hitch	Cat I
Tractor Power (HP) 20-30	5 0	Tractor Power (HP)	20-30
Weight with standard bucket (kg lbs) 375 / 827	kg		375 / 827



*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

BENEFITS AND ADVANTAGES

- Curved Boom helps in better Visibility.
- Easy to attach and detach while not in operation.
- Can cover several range of terrain types.
- Designed to move easily over the rough terrain.
- High breakout force helps in operating at hard surfaces.