



FURROW RIDGER

DESCRIPTION

Worldtrac Furrow Ridger is the primary soil tillage equipment which is mounted and trailed from tractor's hydraulic unit and universal 3 point linkage system. As per crop it helps in making perfect ridge and also helps in uprooting unwanted roots and weeds.



FEATURES



ROBUST PIPE FRAME.



HEAVY DUTY POINTED FURROW



EASY TO ATTACH WITH 3 POINT LINKAGE



EASY FURROW WIDTH ADJUSTMENT

TECHNICAL SPECIFICATIONS

Furrow Ridger		
Model	WT-FR5	WT-FR7
No. of Bottom	5 Bottom	7 Bottom
Width (mm / Inch)	3050 / 120.1	4495 / 177
Length (mm / Inch)	940 / 37	965 / 38
Height (mm / Inch)	1270 / 50	
Furrow to Furrow Distance (mm / Inch)	660 / 26	
Furrow Blade Height (mm / Inch)	305 / 12	
Weight (Kg. / lbs Approx.)	355 / 783	480 / 1058
Tractor Power (HP)	75	90

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

BENEFITS AND ADVANTAGES

- Available in 2 bottoms, 4 bottoms & 6 Bottoms to make one ridge, two ridges & three ridges respectively.
- It has heavy duty box type frame.
- High quality boron steel disc with 48-52 HRC hardness.
- Size and depth of the ridge can be adjusted.