

POWER SERIES

DESCRIPTION

Worldtrac Power Series are intended for big farms and farm contractors. This is a large rotary tiller designed to work in particularly toughest challenging conditions. Its robust structure and wide number of features allows it to achieve excellent results in any type of field conditions in different agroclimatic zones.



FEATURES











TECHNICAL SPECIFICATIONS

		Power Series						
0	Model	WT-CS-5	WT-CS-5.5	WT-CS-6	WT-CS-7	WT-CS-8	WT-CS-9	WT-CS-10
	Size (in feet / m)	5 / 1.5	5.5 / 1.7	6 / 1.8	7 / 2.1	8 / 2.4	9 / 2.7	10/3
	Working Width (mm / Inch)	1630 / 64.2	1805 / 71.1	1885 / 74.2	2135 / 84.1	2340 / 92.1	2825 / 111.2	3045 / 119.9
	Gear Box	Single Speed						
್ಥ	Side Transmission	Gear Drive						
u	Types of Blades	L /C (Optional)						
u	No of Blades	36	36	42	48	54	60	66
	Gear Box Overload Protection	Shear Bolt						
kg	Weight (kg / lbs)	421 / 928	441 / 972	451 / 994	485 / 1069	537 / 1184	571 / 1259	641 /1413
6 6	Tractor Power (HP)	45-55	50-60	55-65	60-70	65-75	75-85	80-90

^{*}Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

BENEFITS AND ADVANTAGES

- Multiple depth control holes suitable for all applications.
- Highly durable crown & pinion which has great ability to distribute the heat generated by friction and hence increases the longevity of gearbox.
- 55mm bigger diameter makes transmission shaft much more stronger.
- Bearings having high load bearing capacity, ensure minimum wear & tear even in toughest soil conditions.
- Greater pulverization improves soil structure in terms of water & air retention.