

SUB-SOILER

DESCRIPTION

Worldtrac Sub-Soiler is special equipment used to break the compacted soil restricting the movement of water, air & roots which eventually increases the survival rate and even growth of crops/plants.

It increase water, air and plant communication in the soil in the best way. Subsoiler breaks a second layer of soil, it penetrates more than other primary implements.

It works effectively in hard soil and helps to increase efficiency of secondary implements

FEATURES





ANGLED WINGS AND **HEAVY DUTY POINTED CHISEL**





TECHNICAL SPECIFICATIONS

		Sub-Soiler			
ð	Model	WT-SS1	WT-SS2	WT-SS3	WT-SS5
र्गर	Length (mm / Inch)	660 / 26	1065 / 41.9		1525 / 60
र्गर ।	Width (mm / Inch)	685 / 27	1790 / 70.5		3375 / 132.9
रगरा	Height (mm / Inch)	1250 / 49.2			1270 / 50
	Working Width (mm / Inch)	Single Shank	750-790 / 29.5-31.1	1490-1530 / 58.7-60.2	2950-3050 / 116.1-120.1
mtuntuntun →	Working Depth (mm / Inch)	600 / 23.6			800 / 31.5
///	No. of Shanks	1	2	3	5
kg	Weight (Kg. / Ibs Approx.)	130 / 287	295 / 650	355 / 783	730 / 1609
୶୕୕	Tractor Power (HP)	35-45	55-60	75-90	100+

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development

BENEFITS AND ADVANTAGES

- Rugged Heavy Duty Frame to sustain sudden impact and permanent loads on field.
- The angled wings lift and shatter the hard pan that builds up due to compaction and heavy duty pointed chisel and steel shank rips deeply through hard, compacted soil.
- Space between Tynes can be adjusted easily
- Self-sharpening Heavy Duty Pointed Reversible Boron Steel Shovels for better performance
- Optional Support tyres to support and control depth while field operations for 5 Tyne Subsoiler.



