



TRAILER

DESCRIPTION

The trailer is another essential farm equipment that can be utilized for transporting various things for all purposes and activities.



FEATURES



HYDRAULIC UNLOADING



HEAVY DUTY FRAME



HIGH STRENGTH
CORRUGATED SHEET



HIGH-GRADE HUBS AND AXLE



DURABLE TAPER
ROLLER BEARINGS



OPTIONAL SEPARATE
BRAKES



COLLAPSIBLE SIDE PANEL

BENEFITS AND ADVANTAGES

- ⊙ Hydraulic lift helps in unloading material quickly.
- ⊙ Heavy duty frame helps in doing heavy operations.
- ⊙ A high-grade hub, axle & tipping mechanism enhance the life of the trailer.
- ⊙ Easy attachment and detachment from the tractor makes it more comfortable in operation.
- ⊙ Optional Separate brakes to trolley makes easy for parking at inclined road.
- ⊙ Taper roller bearing enhances service life .
- ⊙ Collapsible side panels (optional) ensures hassle free unloading .



TECHNICAL SPECIFICATIONS

Tipping Trailer Single Axle						
Model	WTSTT-1	WTSTT-2	WTSTT-3	WTSTT-5	WTSTT-8	WTSTT-10
Loading Capacity (kg / lbs)	1000 / 2205	2000 / 4409	3000 / 6614	5000 / 11023	8000 / 17637	10000 / 22046
Dimension (mm / Inch)	2000x1200x355 / 78.7x47.2x14	2130x1370x533 / 83.9x53.9x21	2435x1830x610 / 95.9x72x24	3050x1830x610 / 120.1x72x24	3650x1830x610 / 143.7x72x24	3960x1830x610 / 155.9x72x24
Main Chassis (mm / Inch)	100x50 / 3.9x2		125x65 / 4.9x2.5	150x75 / 5.9x2.9	200x75 / 7.9x2.9	
Floor Sheet (mm / Inch)	3 / 0.12			4 / 0.16		
Side Wall Sheet (mm / Inch)	2 / 0.08					
Tyre	12/16	600x16	750x16	900x16		
Ring Hitch Dia (mm / Inch)	45 / 1.8		50 / 2			
Hyd.Cylinder Cap. (M. Ton / Ton)	2 / 2.2	3 / 3.3	10 / 11	15 / 16.5	20 / 22.04	
Axle (Break Optional) mm / Inch	50 / 2	65 / 2.5	75 / 2.9		90 / 3.5	
Axle Bearing	32209 Inner 32209 Outer	32209 Inner 32210 Outer	32213 Inner 32216 Outer			
Weight (Kg / lbs)	300 / 661	600 / 1323	915 / 2017	1250 / 2756	1550 / 3417	1800 / 3968
Tractor Power (HP)	18-26	20-26	35-50	50-70	70-90	90-120

Tipping Trailer Double Axle Turn Table			
Model	WTDTT-5	WTDTT-8	WTDTT-10
Loading Capacity (kg / lbs)	5000 / 11023	8000 / 17637	10000 / 22046
Dimension (mm / Inch)	3050X1830x610 / 120.1x72x24	3650X1830x610 / 143.7x72x24	3960X1830x610 / 155.9x72x24
Main Chassis (mm / Inch)	150X75 / 5.9x2.9	200X75 / 7.9x2.9	
Floor Sheet (mm / Inch)	4 / 0.16		
Side Wall Sheet (mm / Inch)	2 / 0.08		
Tyre	900X16		
Ring Hitch Dia (mm / Inch)	50 / 2		
Hyd Cylinder Cap. (M. Ton / Ton)	15 / 16.5	20 / 22.4	
Axle (Break Optional) mm / Inch	75 / 2.9		90 / 3.5
Axel Bearing	32213 Inner 32216 Outer		
Weight (Kg / lbs)	1500 / 3307	1800 / 3968	2100 / 4630
Tractor Power (HP)	50-70	70-90	90-120

Non Tipping Trailer Single Axle					
Model	WTSNTT-2	WTSNTT-3	WTSNTT-5	WTSNTT-8	WTSNTT-10
Loading Capacity (kg / lbs)	2000 / 4409	3000 / 6614	5000 / 11023	8000 / 17637	10000 / 22046
Dimension (mm / Inch)	2130x1370x533 / 83.9x53.9x21	2435x1830x610 / 95.9x72x24	3050x1830x610 / 120.1x72x24	3650x1830x610 / 143.7x72x24	3960x1830x610 / 155.9x72x24
Main Chassis (mm / Inch)	100x50 / 3.9x2	125x65 / 4.9x2.5	150x75 / 5.9x2.9	200x75 / 7.9x2.9	
Floor Sheet (mm / Inch)	3 / 0.12		4 / 0.16		
Side Wall Sheet (mm / Inch)	2 / 0.08				
Tyre	600x16	750x16	900x16		
Ring Hitch Dia (mm / Inch)	45 / 1.8	50 / 2			
Axle (Break Optional) mm	65 / 2.5	75 / 2.9		90 / 3.5	
Axle Bearing	32209 Inner 32210 Outer	32213 Inner 32216 Outer			
Weight (Kg / lbs)	500 / 1102	800 / 1764	1100 / 2425	1400 / 3086	1650 / 3638
Tractor Power (HP)	20-26	35-50	50-70	70-90	90-120

Non Tipping Trailer Double Axle Turn Table			
Model	WTDNTT-5	WTDNTT-8	WTDNTT-10
Loading Capacity (kg / lbs)	5000 / 11023	8000 / 11637	10000 / 22046
Dimension (mm / Inch)	3050X1830x610 / 120.1x72x24	3650X1830x610 / 143.7x72x24	3960X1830x610 / 155.9x72x24
Main Chassis (mm / Inch)	150X75 / 5.9x2.9	200X75 / 7.9x2.9	
Floor Sheet (mm / Inch)	4 / 0.16		
Side Wall Sheet (mm / Inch)	2 / 0.08		
Tyre	900X16		
Ring Hitch Dia (mm / Inch)	50 / 2		
Axle (Break Optional) (mm / Inch)	75 / 2.9	75 / 2.9	90 / 3.5
Axle Bearing	32213 Inner 32216 Outer		32213 Inner 31216 Outer
Weight (Kg / lbs)	1350 / 2976	1650 / 3638	1950 / 4299
Tractor Power (HP)	50-70	70-90	90-120